



|               |       |
|---------------|-------|
| Project:      |       |
| Location:     |       |
| Model#: AR-N7 | Type: |
| Client:       | Qty:  |
| Prepared by:  | Date: |

#### SERIES SPECIFICATIONS

To supply and install JL-240 series of twist-lock photocontrol receptacles, designed for the fixtures intended to have an ANSI C136.10-2006 receptacle to fit a twist-lock photocontrol. This series conforms to ANSI C136.41-2013 to allow a LED lamp multi-controlled through the receptacle. This series offers 2 or 4 gold-plated low voltage pads on the top surface to fit photocontrols that have ANSI C136.41 conforming spring contacts, and offers male quick connectors at the rear/back for signal connection. This series also offers 360 degree rotation limiting feature to conforming to ANSI C136.10 requirements. Both JL-240X and JL-240Y have been recognized, and JL-200Z14 has been listed by UL to applicable US and Canadian safety standards, under file E188110, Vol.1 & Vol.2.NEMA-7 Twist lock receptacle to be used with the Tam-lite ARPS, ARPT and ARWP series of fixtures

#### PERFORMANCE SPECIFICATIONS

**Environmental Rating(s):** IP44

**Ambient Operating Temp:** -40DegC to  
+70 Deg C

**UL Classification:** Locking Type  
Photocontrols UL773

**Limited Product Warranty:** 1 year

**Sound Transmission Class Rating:**

#### ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120-480V

**Input Frequency:** 50/60Hz

**Fixture Draw:** 1000W Tungsten, 1800VA  
Ballast, 1.5VA

#### PHYSICAL SPECIFICATIONS

**Finish Colour:** Black

**Wiring:** Internal

**Housing Material:** Plastic

#### SHIPPING INFORMATION

**OrderingCode(s):** AR-N7

**Box Quantity:** 1

**Box Dimensions (L-W-H):** 84x66x80 mm

**Box Weight:** 0.09 kg