



Project:	
Location:	
Model#: DL6MED/IC/R	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply and install Tam-lite DL6MED Series of line voltage recessed Housing as specified. The Housing shall operate at 120VAC. Lamps shall be as specified, medium base lamps up to a maximum of the rated lamp wattage on the fixture nameplate. The lamps shall not be supplied with the fixture. The fixture shall be c-UL-us approved.

PERFORMANCE SPECIFICATIONS

NEMA Type: IC Rated
Limited Product Warranty: 1 Year

Environmental Rating(s): IC Rated, Air
Tight ASTM E283

UL Classification: Damp Location Listed

LED SPECIFICATIONS

Source Type: Incandescent

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac

Input Frequency: 60 Hz

Max Operating Case Temperature: 90°C

PHYSICAL SPECIFICATIONS

Finish Colour: Galvanized
Mounting: Compression Clamp

Finish Type: Galvanized Steel
Housing Material: Galvanized Steel

Wiring: 7x 7/8" Knockouts

SHIPPING INFORMATION

Ordering Code(s): DL6MED/IC/R
Carton Weight: 9.5lbs/4.3Kgs

Carton Quantity: 6

Carton Dimensions (I-W-H):
533x508x203mm