



Project:	
Location:	
Model#: DL6MED/SL/IC	Type:
Client:	Qty:
Prepared by:	Date:

SERIES SPECIFICATIONS

To supply and install Tamlite DL6MED Series of line voltage recessed slope Housing as specified. The Housing shall operate at 120VAC. Lamps shall be as specified, medium base lamps up to a maximum of the rated lamp wattage on the fixture nameplate. The lamps shall not be supplied with the fixture. The fixture shall be c-UL-us approved.

PERFORMANCE SPECIFICATIONS

NEMA Type: IC Rated
Limited Product Warranty: 1 Year

Environmental Rating(s): IC Rated, Air
Tight ASTM E283

UL Classification: Damp Location Listed

LED SPECIFICATIONS

Source Type: Incandescent

ELECTRICAL SPECIFICATIONS

Input Voltage: 120-277Vac

Input Frequency: 60 Hz

Max Operating Case Temperature: 90°C

PHYSICAL SPECIFICATIONS

Finish Colour: Galvanized
Mounting: Compression Clamp

Finish Type: Galvanized Steel
Housing Material: Galvanized Steel

Wiring: 7x 7/8" Knockouts

SHIPPING INFORMATION

OrderingCode(s): DL6MED/SL/IC
Carton Weight: 13lbs/5.9Kgs

Carton Quantity: 4

Carton Dimensions (I-W-H):
610x489x222mm