



|                     |       |
|---------------------|-------|
| Project:            |       |
| Location:           |       |
| Model#: DL6MED_IC_R | Type: |
| Client:             | Qty:  |
| Prepared by:        | Date: |

#### SERIES SPECIFICATIONS

To supply Tam-lite DL6MED Series of line voltage recessed Housing as specified. The Housing shall operate at 120Vac. Lamps shall be as specified, medium base lamps up to a maximum of the rated lamp wattage on the fixture nameplate. The lamps shall not be supplied with the fixture. The fixture shall be c-UL-us approved.



#### PERFORMANCE SPECIFICATIONS

**NEMA Type:** IC Rated  
**Certification Standards:** cULus

**Environmental Rating(s):** IC Rated, Air  
Tight ASTM E283  
**Limited Product Warranty:** 1 Year

**UL Classification:** Damp Location Listed

#### LED SPECIFICATIONS

**Source Type:** Incandescent

#### ELECTRICAL SPECIFICATIONS

**Input Voltage:** 120Vac

**Input Frequency:** 50-60Hz

**Max Operating Case Temperature:** 90C

#### PHYSICAL SPECIFICATIONS

**Finish Colour:** Galvanized  
**Mounting:** Compression Clamp

**Finish Type:** Galvanized Steel  
**Housing Material:** Galvanized Steel

**Wiring:** 7x 7/8" Knockouts

#### SHIPPING INFORMATION

**OrderingCode(s):** DL6MED/IC/R  
**Carton Weight:** 4.3

**Carton Quantity:** 6

**Carton Dimensions (L-W-H):** 533 x 508 x  
203 mm