



|                   |       |
|-------------------|-------|
| Project:          |       |
| Location:         |       |
| Model#: HBX100-WG | Type: |
| Client:           | Qty:  |
| Prepared by:      | Date: |

## SERIES SPECIFICATIONS

To supply the Tamlite HBX-100 wire guard



## ELECTRICAL SPECIFICATIONS

**Dimming:** 0-10Vdc, (0% Min Light Level)

## SHIPPING INFORMATION

**OrderingCode(s):** HBX100-WG

**Box Weight:** 0.75 kg

**Box Quantity:** 1

**Box Dimensions (L-W-H):** 655 x 295 x 85 mm

## SERIES ARCHITECTURE

### Series Architecture

| HBX - - - - - |         |      |     |       |          |               |         |             |        |       |                       |
|---------------|---------|------|-----|-------|----------|---------------|---------|-------------|--------|-------|-----------------------|
| Part          | Wattage |      | CCT |       | Mounting |               | Voltage |             | Finish |       | Accessories           |
| HBX           | 50      | 50W  | 30K | 3000K | [Blank]  | Suspended     | UNV     | 120-277 VAC | WH     | White | O Occupancy Sensor    |
|               | 100     | 100W | 40K | 4000K | SM       | Surface Mount | 347     | 347 VAC     |        |       | WG Wire Guard         |
|               | 150     | 150W | 50K | 5000K | PM       | Pendant Mount | WRV     | 120-347 VAC |        |       | SM Surface Mount Kit  |
|               | 200     | 200W |     |       |          |               |         |             |        |       | PM Pendant Mount Kit  |
|               |         |      |     |       |          |               |         |             |        |       | C10 10 ft Cabtire Set |
|               |         |      |     |       |          |               |         |             |        |       | OC-REM PIR Programer  |